

2' x 2' 40W CCT Selectable LED Flat Panel with Emergency Battery Backup (70692)



Reorder Number 70692
Pack Size 1 each

- Emergency Mode provides at least 90 minutes of battery backup in the event of a power loss
- Backup battery and test switch already integrated – no additional wiring required
- 2' x 2' size – easily fits into standard T-bar grid ceilings
- Can also be surface or suspension mounted
- CCT selectable – panel easily switches between 3500K, 4000K and 5000K
- Precision micro-optics create uniform, glare-free light evenly distributed over entire panel
- Lightweight and ultra-thin (1.5") – ideal for both new construction and retrofit applications
- High quality construction – steel housing and white powder coated steel frame create the ultimate in durability
- 110 lm/W - cost-effective solution for high lumen output
- High efficiency, dimmable driver (0-10V)
- Suitable for damp locations
- 100-277V
- 50,000 hour rated lifetime
- 5-year Limited Warranty

Specifications

Model	BP22-W40-3CCT-EM	Base	N/A
Lumen Output (lm)	4400 (1100 lm in EM)lm	Color Temperature	3500/4000/5000K
Part Number	70692	Design life (hours)	50000 Hours
Efficacy	110lm/W	Operating Temperature	-20°C to 40°C
Wattage	40 (8W in EM)W		
CRI	0-10V		
Voltage	40 (8W in EM)V		
Dimmable	0-10V		



Product Information			
L x D x H (In)	23.74 x 23.74 x 2.80 (60.3 x 60.3 x 7.11 in cm)	Weight (lbs)	7.96 lbs (3.61 kg)
Packaging Information			
UPC#	02394270692 2	Unit Quantity	1 each
Pallet Quantity	12 (1 each)	Layers Per Pallet	1
Master Case Information			
L x D x H (In)	26.69 x 5.71 x 26.97 (67.79 x 14.5 x 68.5 in cm)	Weight (lbs)	12.67 lbs (5.75 kg)
UPC#	5002394270692 7	Quantity	1 (1 each)
Shipping Information			
Available Ship Date	In Stock	Country of Origin	CN
Tariff Code	9405.10.6020	Warranty	5 Year Warranty
Minimum Order Qty	1 (1 each)		

Keywords

70692,#70692,2' x 2' 40W CCT Selectable LED Flat Panel with Emergency Battery Backup, 2' x 2' LED Flat Panel, 2' x 2' panel, Flat panel, Fluorescent tube replacement, T8 replacement, office lighting, corporate lighting, lighting for schools, hospital lighting, energy efficient lighting, dimmable flat panel, 0-10V dimming, LED for T-bar grid, lightweight LED panel, thin LED panel, 2x2 panel, surface mount flat panel, CCT selectable panel, 3500K panel, 4000K panel, 5000K panel, 4400 lumens, 4400 lumen panel, EM panel, panel with EM backup, emergency backup panel, panel with emergency backup

Compliance Information

Proposition 65 Chemical(s):

- Bisphenol-A

Proposition 65 Warning Statement:

WARNING: This product can expose you to Bisphenol-A ,which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <https://NACSmart.com>

Image URL:

https://NACSmart.com/media_img/P65_Bisphenol-A.jpg

Certifications

