

2' x 2' 40W CCT Selectable LED Flat Panel with Emergency Battery Backup

- Emergency Mode provides at least 90 minutes of battery backup in the event of a power loss
- Backup battery and test switch already integrated – no additional wiring required
- 2' x 2' size – easily fits into standard T-bar grid ceilings
- Can also be surface or suspension mounted
- CCT selectable – panel easily switches between 3500K, 4000K and 5000K
- Precision micro-optics create uniform, glare-free light evenly distributed over entire panel
- Lightweight and ultra-thin (1.5") – ideal for both new construction and retrofit applications
- High quality construction – steel housing and white powder coated steel frame create the ultimate in durability
- 110 lm/W - cost-effective solution for high lumen output
- High efficiency, dimmable driver (0-10V)
- Suitable for damp locations
- 100-277V
- 50,000 hour rated lifetime
- 5-year Limited Warranty



Specifications	
Model	BP22-W40-3CCT-EM
Part Number	70692
Color Temperature	3500/4000/5000K
Lumen Output	4400 (1100 lm in EM)lm
Wattage	40 (8W in EM)W
Power Factor	0.9
CRI	0-10V
Efficacy	110lm/W
Dimmable	0-10V
Voltage	40 (8W in EM)V
Operating Temperature	-20°C to 40°C
Base	N/A
Weight	127.36 oz.
Dimensions	23.74 x 2.80 x 23.74 in
Rated Lifetime	50000 Hours
Warranty	5 Year Warranty
DLC Product Listing	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces (V5)

Certifications:



2' x 2' 40W CCT Selectable LED Flat Panel with Emergency Battery Backup

Additional Images:



Diagrams:

